



## **Superior Mark® Carpet Tape Specification**

### **Floor Marking Carpet Tape:**

Superior Mark® aisle marking Carpet Tapes are designed to be overlaid on indoor carpet surfaces. Superior Mark® Carpet Tape will create awareness throughout buildings and classrooms by delineating perimeters, equipment storage, desk, safety hazards, walkways, and more. Superior Mark® Carpet Tape is available in 2", 4", and 6" widths in all colors and patterns.

### **Composition:**

Superior Mark® Carpet Tape is a proprietary polymer material with a minimum Shore A Durometer of 95+. Superior Mark® Carpet Tape is supplied with a pre-applied hook side layer that is permanently attached to a .005" minimum recessed slot. The tape shall have a minimum trouser tear resistance exceeding 250 lbF/in when tested according to ASTM D 1938-08. The top layer shall be completely smooth to discourage dirt collection.

### **Thickness:**

Superior Mark® Carpet Tape does not exceed .034" thick and features a gradual decline in thickness causing a downward beveled edge to be formed on each side. The bottom side shall contain a recessed slot .005" deep that contains the hook and loop fastener layer.

### **Applicability to Indoor Floor Surfaces:**

Superior Mark® hook and loop backed Carpet Tape must be applied to clean, industrial grade, short fiber carpet surfaces.

### **Pigmentation:**

Superior Mark® Carpet Tapes are selected and blended to provide a floor marking tape that is color stable and consistently colored throughout its thickness. All colors and patterns are available including photo-realistic images.

### **Physical Properties:**

Minimum tensile strength 3000.00 per ASTM D412 Minimum elongation 100 per ASTM D634 Minimum Tear Die C 570 per ASTM D634